



Premium Masking Solutions

## Q1® Handy Masking Paper

Q1® Handy Masking Paper is a high quality paper and makes masking up quick and effective for both brush and spray painting methods.

Suitable for both water and solvent based paints and available in two sizes, the Q1® Handy Masking Paper is ideal for protecting large areas from over spray as well as quickly covering beams, sills and corncicing.



### Features & Benefits

- High quality paper to prevent drips and flaking
- Compatible with solvent and water-based paints
- Suitable for use with masker dispenser
- Ideal for protecting doors and windows frames, beams and for general purpose surface protection

### Available Colour

Kraft Brown

### Product Reference

Part#	Size	Pcs/ Case
Q1MP15	15 cm x 55 m	6 rolls/ box
Q1MP30	30 cm x 55 m	6 rolls/ box

### Technical Data Sheet

Characteristics	Unit	Value	Test method
Basis weight	g/m <sup>2</sup>	40	
Breaking length (MD)	m	4.800	UNI EN ISO 534
Breaking length (CD)	%	2.500	UNI EN ISO 534
Burst (Müllen)	kPa	85	UNI EN ISO 534
Sizing COBB 60	g	<18	UNI EN ISO 534



---

**Additional Information****Storage & Handling**

Q1® Premium Masking Solutions must be stored in a dry location, protected from direct sunlight exposure and from freezing. Storage temperatures should be as close as possible to room temperature; suggested storage temperature should range from 59°F / 15°C to 77°F / 25°C with max. relative humidity of 50%. Do not store tapes and related products in the paint booth during bake cycles.

Make sure the surface you wish to place the tape on is cleaned, dried and free from oil and dust. It is suggested not to apply the tape with temperatures lower than 50°F / 10°C. With a storage temperature lower than 50°F / 10°C, it is always suggested temperature reconditioning of the tape at room temperature (79°F / 15°C - 59°F / 25 °C) before its use. We always recommend testing material in relation to the required applications.

**Shelf life from date of manufacture**

No yellowing and < 10% loss in performance at 73.4°F / 23 °C, 50% humidity is considered 12 months Q1® Premium Masking Solutions does not take responsibility for the defective material if is not stored and used in accordance with the conditions listed above.

**Technical Information Disclaimer**

The technical information, suggestions and other statements contained in this documents have been compiled for your guidance and usage. Information is based on experience and tests that Q1® Premium Masking Solutions believe are reliable. The accuracy or completeness of such information is not guaranteed. Q1® Premium Masking Solutions has no control about conditions in which products are used, stores or handles. The above information doesn't constitute a warranty.

**Product Use**

Q1® would advise that there are many factors beyond Q1® control but within the users knowledge that can affect the use and performance of Q1® products. Q1® remind the user of the products to make sure that its range is used as per the instructions printed above. It is the users sole responsibility to determine that all preparation has been correctly carried out and that the working conditions are as per Q1® literature.