



Premium Masking Solutions

Q1® Scrim Tape

Q1® Scrim tape is a high quality scrim tape made of fiberglass and coated with adhesive glue on one side. It is used on the plasterboard gap to strengthen the strength of the wall. This product is the perfect tool for any plasterboarding project, joining your boards and providing a smooth finish. The mesh of the tape allows it to contain the jointing compound during plastering, creating a strong joint and the holes between the threads allow the plaster to cover all areas for a seamless finish when skimmed. In fact, the threads act as a reinforcing mesh and stop the joints from cracking as the adjacent plasterboard panels move with expansion, contraction and human action



Features

- Self-adhesive and can be re-positioned
- Eliminates need for pre-plastering
- Extra reinforcement when joining plasterboards
- Eliminates blisters and bubbles

Available Colour

White

Product Reference

Part#	Size	Rolls/ Box
Q1ST48	48 mm x 90 m	24 rolls/ box

Technical Data Sheet

Characteristics	Value	Test method
Total Weight	65 g/m ²	ISO 536
Tensile strength warp	> 120 N/cm	AFERA 5004/PSTC 131
Tensile strength weft	> 140 N/cm	AFERA 5004/PSTC 131

Uses

- For joint finishing, crack and hole repair.
- For drywall and plaster walls and ceilings.

Application

- Ensure surfaces are clean, free from dust and dry.
- Remove outer packaging from roll of tape.
- Peel required amount of tape from roll, pressing firmly into place whilst unrolling.
- Cut with a knife or tear when finished



Additional Information**Storage & Handling**

Q1® Premium Masking Solutions must be stored in a dry location, protected from direct sunlight exposure and from freezing. Storage temperatures should be as close as possible to room temperature; suggested storage temperature should range from 14°F / -10°C to 122°F / 50°C with max. relative humidity of 50%. Do not store tapes and related products in the paint booth during bake cycles.

Make sure the surface you wish to place the tape on is cleaned, dried and free from oil and dust. It is suggested not to apply the tape with temperatures lower than 50°F / 10°C. With a storage temperature lower than 50°F / 10°C, it is always suggested temperature reconditioning of the tape at room temperature (79°F / 15°C - 59°F / 25 °C) before its use. We always recommend testing material in relation to the required applications.

Technical Information Disclaimer

The technical information, suggestions and other statements contained in this documents have been compiled for your guidance and usage. Information is based on experience and tests that Q1® Premium Masking Solutions believe are reliable. The accuracy or completeness of such information is not guaranteed. Q1® Premium Masking Solutions has no control about conditions in which products are used, stores or handles. The above information doesn't constitute a warranty.

Product Use

Q1® would advise that there are many factors beyond Q1®' control but within the users knowledge that can affect the use and performance of Q1® products. Q1® remind the user of the products to make sure that its range is used as per the instructions printed above. It is the users sole responsibility to determine that all preparation has been correctly carried out and that the working conditions are as per Q1® literature.