

Q1® Cover All

The Q1® Cover All is the perfect solution for rapid coverage of large areas to protect carpets, floors and furniture from paint, dust and spills even in the messiest of projects.

Thanks to an exclusive patented system it is faster and easier to unfold and open out compared to others products. This sheet is electrostatically charged so that it doesn't slip or flutter when you pass by.



Features & Benefits

- Fast and easy unfolding
- Provides furniture and floor protection from overspray, dust and spills
- Ideal for properly covering and draping goods in storage
- Excellent adherence on all surfaces

Available Colour

Clear

Product Reference

Part#	Size	Pcs/ Case
Q1CA09	4 m x 25 m	15 rolls/ case

Technical Data Sheet

Characteristics	Unit	Value	Test method
Total Weight	gr	850	
Total Thickness	μ	9	
Size	m ²	100	
Melt flow index	gr/10'	0.28/0.38	UNI EN ISO 1133
Density	gr/cm ³	0.949/0.957	ISO 1183
Tensile stress	MPa	35	ISO 527
Yield stress	MPa	24	ISO 527
Breaking elongation		60	ISO 868

Additional Information**Storage & Handling**

Q1® Premium Masking Solutions must be stored in a dry location, protected from direct sunlight exposure and from freezing. Storage temperatures should be as close as possible to room temperature; suggested storage temperature should range from 59°F / 15°C to 77°F / 25°C with max. relative humidity of 50%. Do not store tapes and related products in the paint booth during bake cycles.

Make sure the surface you wish to place the tape on is cleaned, dried and free from oil and dust. It is suggested not to apply the tape with temperatures lower than 50°F / 10°C. With a storage temperature lower than 50°F / 10°C, it is always suggested temperature reconditioning of the tape at room temperature (79°F / 15°C - 59°F / 25 °C) before its use. We always recommend testing material in relation to the required applications.

Shelf life from date of manufacture

No yellowing and < 10% loss in performance at 73.4°F / 23 °C, 50% humidity is considered 12 months Q1® Premium Masking Solutions does not take responsibility for the defective material if is not stored and used in accordance with the conditions listed above.

Technical Information Disclaimer

The technical information, suggestions and other statements contained in this documents have been compiled for your guidance and usage. Information is based on experience and tests that Q1® Premium Masking Solutions believe are reliable. The accuracy or completeness of such information is not guaranteed. Q1® Premium Masking Solutions has no control about conditions in which products are used, stores or handles. The above information doesn't constitute a warranty.

Product Use

Q1® would advise that there are many factors beyond Q1®' control but within the users knowledge that can affect the use and performance of Q1® products. Q1® remind the user of the products to make sure that its range is used as per the instructions printed above. It is the users sole responsibility to determine that all preparation has been correctly carried out and that the working conditions are as per Q1® literature.