

## Q1® Pre Taped Masking Paper

Q1® Pre-taped Masking Paper is the ideal solution for protecting surfaces against paint splatters or drips. It is for interior use during any painting and decorating project. Measuring 180mm X 25m and 300mm X 25m, it is the right size for the protection of skirting boards, architraves, window frames and light switches.

It adheres without fault to wood and metal and conforms well to difficult curves or corners, featuring quick-stick, with reliable clean removal without leaving residue.



### Features & Benefits

- Ideal for covering small surfaces
- Suitable for indoor applications
- Offers fast masking of critical areas
- Clean removal without leaving residue
- Compatible with all popular paints and lacquers
- Flexible and conformable performance

### Available Colour

Tape: Sun Yellow | Paper: Kraft Brown

### Product Reference

Part#	Size	Pcs/ Case
Q1MP180	180 mm x 25 m	40 rolls/ case
Q1MP300	300 mm x 25 m	20 rolls/ case

### Technical Data Sheet

Tape			
Characteristics	Unit	Value	Test method
Total Weight	g/m <sup>2</sup>	103	ISO 536
Total Thickness	mm	0.130	Internal Method
Adhesion to steel plate	N/cm	2.3	AFERA 5001/PSTC 101
Tensile strenght	N/cm	42	AFERA 5004/PSTC 131
Elongation at break	%	8	AFERA 5004/PSTC 131
Temperature resistance	°C	90 (1 hour)	
Paper			
Total Weight	g/m <sup>2</sup>	35	Internal Method
Tensile strenght	kN/m	MD 3.78 – CD 1.54	ISO 1924
Tear resistance	mN	MD 210 – CD 280	ISO 21974
Sizing COBB 60	g/m <sup>2</sup>	30 max	ISO 535
Moisture	%	5 - 9	ISO 287



---

**Additional Information****Storage & Handling**

Q1® Premium Masking Solutions must be stored in a dry location, protected from direct sunlight exposure and from freezing. Storage temperatures should be as close as possible to room temperature; suggested storage temperature should range from 59°F / 15°C to 77°F / 25°C with max. relative humidity of 50%. Do not store tapes and related products in the paint booth during bake cycles.

Make sure the surface you wish to place the tape on is cleaned, dried and free from oil and dust. It is suggested not to apply the tape with temperatures lower than 50°F / 10°C. With a storage temperature lower than 50°F / 10°C, it is always suggested temperature reconditioning of the tape at room temperature (79°F / 15°C - 59°F / 25 °C) before its use. We always recommend testing material in relation to the required applications.

**Shelf life from date of manufacture**

No yellowing and < 10% loss in performance at 73.4°F / 23 °C, 50% humidity is considered 12 months Q1® Premium Masking Solutions does not take responsibility for the defective material if is not stored and used in accordance with the conditions listed above.

**Technical Information Disclaimer**

The technical information, suggestions and other statements contained in this documents have been compiled for your guidance and usage. Information is based on experience and tests that Q1® Premium Masking Solutions believe are reliable. The accuracy or completeness of such information is not guaranteed. Q1® Premium Masking Solutions has no control about conditions in which products are used, stores or handles. The above information doesn't constitute a warranty.

**Product Use**

Q1® would advise that there are many factors beyond Q1®' control but within the users knowledge that can affect the use and performance of Q1® products. Q1® remind the user of the products to make sure that its range is used as per the instructions printed above. It is the users sole responsibility to determine that all preparation has been correctly carried out and that the working conditions are as per Q1® literature.