



Premium Masking Paper

Q1® Premium Masking Paper is a high quality 50 gsm paper, created for automotive aftermarket applications.

It is designed to offer protection against primers, varnishes and both water and solvent based paints. The tightly bonded paper protects against fibre contamination and conforms easily to irregular surfaces.



Features

- High quality 50gsm Kraft masking paper
- Specially treated paper
- Excellent resistance to base coats, clear coats, urethanes and water based paints
- Thin paper
- Tightly bonded paper

Benefits

- Good penetration resistance
- Good conformability
- Lint and fibre free
- Helps reduce rework caused by bleed-through
- Easy to handle to help improve productivity
- Helps eliminate rework caused by fiber contamination in paint job

Available Colour

Kraft Brown

Product Reference

Part#	Size
MPO245	45 cm x 200 m
MPO290	90 cm x 200 m
MPO2120	120 cm x 200 m

Technical Data Sheet

Substance	g/qm	48-52	DIN EN ISO 536:2012
Tensile strenght md	N/15mm	>22	DIN EN ISO 1924-2:2009
Tensile strenght cd	N/15mm	>11	DIN EN ISO 1924-2:2009
cd / md relation	%	>40	
Breaking lenght md	mtr.	>3.100	DIN EN ISO 1924-2:2009
Breaking lenght cd	mtr.	>1.600	DIN EN ISO 1924-2:2009
Breaking lenght average	mtr.	>2.350	DIN EN ISO 1924-2:2009
Burst strenght abs.	kPa	>65	DIN EN ISO 2758:2014
Burst strenght rel.	kg/qcm	>1.3	DIN EN ISO 2758:2014
Air resistance (bendtsen)	ml/min	200-600	DIN 53120-1:1998
Sizing COBB 60	g/qm	15-25	DIN EN ISO 2758:2014

How to



Watch our tutorial video on You Tube.

Scan the QR code with your smartphone to learn more about how to use our products.

Additional Information

Q1® Tapes must be stored in a dry location, protected from direct sunlight exposure and from freezing. Storage temperatures should be as close as possible to room temperature; suggested storage temperature should range from 59°F / 15°C to 77°F / 25°C with max. relative humidity of 50%. Do not store tapes and related products in the paint booth during bake cycles.

Make sure the surface you wish to place the tape on is cleaned, dried and free from oil and dust. It is suggested not to apply the tape with temperatures lower than 50°F / 10°C. With a storage temperature lower than 50°F / 10°C, it is always suggested temperature reconditioning of the tape at room temperature (79°F / 15°C - 59°F / 25 °C) before its use. We always recommend testing material in relation to the required applications.

Shelf life from date of manufacture

No yellowing and < 10% loss in performance at 73.4°F / 23 °C, 50% humidity is considered 12 months Q1® Tapes does not take responsibility for the defective material if is not stored and used in accordance with the conditions listed above.

Technical Information Disclaimer

The technical information, suggestions and other statements contained in this documents have been compiled for your guidance and usage. Information is based on experience and tests that Q1® Tapes believe are reliable. The accuracy or completeness of such information is not guaranteed. Q1® Tapes has no control about conditions in which products are used, stores or handles. The above information doesn't constitute a warranty.

Precautionary Information

Refer to Product label description and Material Safety Data Sheet for Health and Safety Information for a proper handling of product. MSDS info available at www.q1tapes.com

Product Use

Q1® Tapes would advise that there are many factors beyond Q1® Tapes' control but within the users knowledge that can affect the use and performance of Q1® Tapes products. Q1® Tapes remind the user of the products to make sure that the Q1® Tapes range is used as per the instructions printed above. It is the users sole responsibility to determine that all preparation has been correctly carried out and that the working conditions are as per Q1® Tapes literature.