



Premium Masking Solutions

Premium Foam Masking Tape

Traditional Masking Tape vs. Foam Masking Tape

Q1® Premium Foam Masking Tape is designed to protect door edges and gaps from overspray while providing a smooth edge reducing time to complete the job. Mask jambs and other apertures quickly and increase profitability.

Traditional flat masking tape can leave paint lines when used inside apertures, or must be rolled in order to create a sort of soft edge. Thanks to its construction, Q1® Premium Foam Masking Tape creates an edge faster than other classic jamb masking techniques. Also dust and other contaminants are sealed in, preventing them from damaging paint job. The tape can also be left in place during the final prep phase to help reduce compound and polish from entering jamb areas.



Features

- Specially designed polyurethane foam structure
- Highly absorbent to avoid any leaking and paint runs
- Flexible
- Easy/clean removal
- Solvent resistant
- Easy roll release in a box dispenser
- 80°C temp rating

Benefits

- Easy to shape on contours, mask and seal all jambs
- Good adhesion to vehicle surfaces and able to withstand paint booth bake cycles
- Prevents overspray from penetrating into the jamb
- Improved productivity by reducing the time required to mask jambs with tape and masking paper
- Leaves no residue

Available Colour

White

Temperature Resistance

80° C.

Product Reference

Q1® Product Number	Q1® Product Description
SE02	13mm x 50 m - box

Technical Data Sheet

Foam	Features Result	Units	Norm	Specification		
	Density	Kg/m ³	UNE-EN ISO 845	28+-2 29.30		
	Hardness	KPa	UNE-EN ISO 33861	4.5+-0.5 4.08		
	Def. Remaining	%	UNE-EN ISO 1586-A	<5 4.90		
	High Tensile	KPa	DIN 53571	>150 228		
Adhesive	Description	Colour/Base	Smell			
	Adhesive thermo fusible - it melts with heat	Transparent/block polymer	Oudourless at room temperature			
Foam physical constants	Temperature	Viscosity				
	180°C	8000+-1000 mPas.				
	170°C	11000+-1500 mPas.				
Chemical resistance	Water	Acid/Base	Fats/Oils	D. Aliphatic	D. Aromatics	D. Alcohols
	Excellent	Good	Good	Poor	Poor	Good

How to



Watch our tutorial video on You Tube.

Scan the QR code with your smartphone to learn more about how to use our products.

Additional Information

Storage & Handling

Q1[®] Tapes must be stored in a dry location, protected from direct sunlight exposure and from freezing. Storage temperatures should be as close as possible to room temperature; suggested storage temperature should range from 15 to 25°C with max. relative humidity of 50%. Do not store tapes and related products in the paint booth during bake cycles.

Make sure the surface you wish to place the tape on is cleaned, dried and free from oil and dust. It is suggested not to apply the tape with temperatures lower than 10°C. With a storage temperature lower than 10°C, it is always suggested temperature reconditioning of the tape at room temperature (15°C - 25 ° C) before its use. We always recommend testing material in relation to the required applications.

Shelf life from date of manufacture

No yellowing and < 10% loss in performance at 23 °C, 50% humidity is considered 12 months Q1[®] Tapes does not take responsibility for the defective material if is not stored and used in accordance with the conditions listed above.

Technical Information Disclaimer

The technical information, suggestions and other statements contained in this documents have been compiled for your guidance and usage. Information is based on experience and tests that Q1[®] Tapes believe are reliable. The accuracy or completeness of such information is not guaranteed. Q1[®] Tapes has no control about conditions in which products are used, stores or handles. The above information doesn't constitute a warranty.

Precautionary Information

Refer to Product label description and Material Safety Data Sheet for Health and Safety Information for a proper handling of product. MSDS info available at www.q1tapes.com

Product Use

Q1[®] Tapes would advise that there are many factors beyond Q1[®] Tapes' control but within the users knowledge that can affect the use and performance of Q1[®] Tapes products. Q1[®] Tapes remind the user of the products to make sure that the Q1[®] Tapes range is used as per the instructions printed above. It is the users sole responsibility to determine that all preparation has been correctly carried out and that the working conditions are as per Q1[®] Tapes literature.